

Salt & Swim[®] 2.0

YEARS OF WARRANTY

3 STANDARD 8000 HOURS

Cell
MADE IN EU

NEW GENERATION SALT CHLORINATOR

- **Salt chlorinator** covering a wide range of chlorine production: 8, 16, 22, 33 gr/h of chlorine
- Production configuration thanks to the **LED display**
- **Transparent cell** for visual checks on production.
Gas detector included as standard
- Detection of presence of a pool cover for adjustment of chlorine production
- **Flow detector kit** as an option
- **5 levels possible** of chlorine production (20, 40, 60, 80, 100%)



INCLUDED



Precise and user-friendly controls thanks to the LED display
Salt & Swim[®] 2.0 changes colour depending on the control selection made, in particular for chlorine production with or without a closed pool shutter.



Installation of the cell in piping
> **Installation in a vertical position, on by-pass,** at the highest point of the installations

SALT & SWIM[®] 2.0

| Description | SASV08CEU | SASV16CEU | SASV22CEU | SASV33CEU |
|-----------------------------|---|-------------------|--------------------|--------------------|
| Production | 8 g/h | 16 g/h | 22 g/h | 33 g/h |
| Chlorine production | 5 levels possible: 20, 40, 60, 80, 100% | | | |
| Pool size up to | 30 m ³ | 75 m ³ | 100 m ³ | 150 m ³ |
| Salt concentration | 3 to 100 g/L | | | |
| Display | LED | | | |
| Protection | IP 65 | | | |
| Superchlorination mode | ● | ● | ● | ● |
| Manual adjustment of Cl % | ● | ● | ● | ● |
| Gas detector | ● | ● | ● | ● |
| Cover detection | ● | ● | ● | ● |
| Alarm | Salt level / flow | | | |
| Closed pool cover detection | Yes | | | |
| Packaging dimensions | 400 x 400 x 210 mm | | | |
| Weight | 9 kg | 9 kg | 10 kg | 10 kg |