

# AquaRite® Flo Advanced



YEARS OF WARRANTY  
**3** STANDARD **4** <sup>TH</sup> 8000 HOURS



## MORE THAN A SALT CHLORINATOR!

- **Salt chlorinator** combined with the control of pool equipments
- Wide range of Chlorine production, 8,16,22,33,55,70 gr/h and 2 items LS **covering the needs of all pools on the market**
- **Transparent cell** to enable a visual check of the production
- **Monitoring** of the filtration pump and the lighting
- No need of an additional transformer for the lighting, **the power is provided directly by the control unit for LED lights up to 50W**
- **pH, ORP kits** and flow sensor available as an option
- Wifi and Ethernet optional connection kits available for a **remote control of the pool equipments**



### INCLUDED



Description		AQR-FLO-AD8	AQR-FLO-AD16	AQR-FLO-AD22	AQR-FLO-AD33	AQR-FLO-AD50	AQR-FLO-AD16LS	AQR-FLO-AD33LS
AQUARITE® FLO ADVANCED	Production	8 g/h	16 g/h	22 g/h	33 g/h	50 g/h	-	-
	Pool size up to	30 m³	75 m³	100 m³	150 m³	200 m³	60 m³	120 m³
	Salt concentration	3 to 100 g/l					1.5 to 100 g/l	
	Display	Graphics display shows present production, cover, pH*, mV*, temp*						
	Protection	IP65						
	Language selection	GB - FR - SP - DE - IT - CZ - PT - NL - PL - HU - RU						
	Superchlorination mode	●	●	●	●	●	●	●
	Manual adjustment of Cl	●	●	●	●	●	●	●
	Lighting management (supply up to 50W)	●	●	●	●	●	●	●
	Filter pump / VSTD pumps management	●	●	●	●	●	●	●
	Cover detection	●	●	●	●	●	●	●
	Smart mode: adjustment of Cl	●	●	●	●	●	●	●
	Flow Switch	-	-	-	-	●	-	-
	Gas detector	●	●	●	●	No	●	●
	Self-cleaning	Programmable up to 999 min						
Alarms	Low salt / no flow / pH (60 minutes)							
Control box dimensions	254 x 298 x 133							
AVAILABLE OPTIONS	pH (with pump)	BKPER-OPTION-PH						
	Rx	E-OPTION-REDOX						
	WiFi	RS3WI-OPTION-W						
	Ethernet	RS3NET-OPTION-L						
	Temperature	T-OPTION-TEMP						

## CONNECTIVITY



Watch the video

\* AquaRite®  
 UV LS /  
 AquaRite® + /  
 AquaRite® Flo  
 Advanced /  
 Control  
 Station